

Geschiktheid voor vloerverwarming					6 mm					
	71 mm	90 mm	120 mm	140 mm	115	140	165	180	210	230
Arura	--									
Vermelho FSC										
Afromosia	++	++				++	+/-			
Afzelia Pachyloba	++	++	+	+	++	++	+/-	+/-		
Afzelia Doussié	++	++	+	+	++	++	+/-	+/-		
Basralocus	--									
Beuken	--									
Gestoomd										
Beuken Premier	--									
Bilinga	--									
Eiken QFQ	++	++	+	+	++	++	+/-	+/-		
Eiken Premier	++	++	+	+	++	++	+/-	+/-	--	--
Eiken 1-bis	++	++	+	+	++	++	+/-	+/-	--	--
Eiken	++	++			++	++	+/-	+/-	--	--
Rustiek Extra										
Eiken Bruut						++	+/-	+/-	--	--
Eiken Rood		--				--				
Amerikaans										
Eik Gest Premier	+	+								
Eik Gest 1-bis	+	+					+/-	+/-		
Eik Gest R E		+					+/-	+/-		
Essen Premier	--									
Guatambu	--									
Ipe FSC	--									
Jatoba	--	--				--				
Jatoba FSC	--									
Kambala	++	++	+	+	++	++	+/-	+/-		
Kambala FSC	++									
Kerouwing	--									
Kerouwing FSC	--									
Kersen	-	-								
Maple	--	--				--				
Mahonie		-								
Merbau	++	++	+	+	++	++	+/-	+/-		
Moabi	--									
Muteneye	+	+	-	-		-		-		
Muiricatiara	--									
Noten	-	-				--				
Padoek	++					++		+/-		
Panga Panga	+									
Purperhart	--					--				
Purperhart FSC	--					--				
Robijn	--	--				--				
Sucupira Preto	--									
Sucupira	--									
Amarelho FSC										
Sucupira	--									
Preto FSC										
Teak	++	++				++				
Wengé	+	+				-	--	--		

++ = zeer geschikt  
+ = geschikt  
+/- = niet onze voorkeur

- = minder tot niet geschikt  
-- = niet geschikt